

PowerWalker VI 2200 LCD

Line-Interactive UPS System

2200VA Line-Interactive UPS

2x Schuko + 2x IEC outlets, RJ11/RJ45 Surge Protection


USB Connection for monitoring

Cold start, built-in boost and buck AVR function

LCD display for status view



Item-No. 10120098



2x Schuko Outlets 2x IEC Outlets AVR (Autom. Voltage Regulator) Fax & Modem Security Port Monitoring Software USB Port

Product Features

PowerWalker VI 2200 LCD is a Line- Interactive UPS which provides high performance and reliable and cost-effective backup power protection. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ11/RJ45 surge protection. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or SMB (small medium business) application.

- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ11/RJ45 surge protection
- Monitoring software included
- LCD Display show UPS status



Backside view



LCD status view

Technical Details

Product Features

Capacity	2200VA/1200W
Input Voltage	230 VAC
Input Voltage Range	170-280VAC \pm 7%
Output Voltage	230 VAC
Voltage Regulation (Battery Mode)	\pm 10%
Output Frequency	50Hz or 60Hz
Frequency Regulation (Battery Mode)	\pm 1Hz
Output Waveform	Simulated Sine Wave

Battery

Type	12V / 9Ah
Quantity	2x
Recharge Time	6h for 90% after complete discharge

Transfer Time

Typical	4-8 ms
----------------	--------

LED Indicators

Indicators	AVR mode, Battery mode, Load level, Battery capacity, Input voltage, Output voltage, Overload alarm, Fault alarm, and Low battery alarm
-------------------	---

Audio Indicators

Battery Mode	Beep every 10 sec
Low Battery	Beep every second
Fault	Continuous Beep
Overload	Beep every 0,5 sec

Full Protection

Discharge prevention	Yes
Deep discharger	Yes
Overcharge	Yes
Overload	Yes

Connections

Interface	USB
Outlets	2x Schuko, 2x IEC
Surge Protection	RJ11/RJ45 (in/out)

Software & System Requirements

Software	WinPower
Operating System	For details visit: www.powerwalker.com/winpower.html
Other	1x USB port

Product Details

Dimensions	365 x 139 x 195 mm
Colour	Black
Weight	10.4 kg
Fan Control	Auto OFF: in LINE mode and if internal voltage \geq 13.4Vdc and load <50% ON: in battery mode, AVR mode and in LINE mode if load is >50%
Model Code	VI 2200 LCD

Environment

Temperature	0°C – 40°C
Humidity	0% - 90% RH (non-condensing)

Package Content

Package Content	PowerWalker VI 2200 LCD, Input Power cable, IEC cable, USB cable, Software CD, Manual
------------------------	---

Logistic Data

Giftbox Language	EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KZ/RS
Manual Language	EN/DE/FR/PL
Dimension/Giftbox	452 x 230 x 292 mm
Weight/Giftbox	11.1
Pieces/Carton	1pcs
Pieces/Palette	42 pcs
Item Number	10120098
EAN	4260074976502
Warranty	24 Month (except battery)

Available accessories



Yuasa 12V/7Ah battery
 Datasheet: [Link](#)
 CSB or Panasonic brand can also be used



Yuasa 12V/9Ah battery
 Datasheet: [Link](#)
 CSB or Panasonic brand can also be used



USB cable
 Item Nr.: 91010011



ATS (Automatic Transfer Switch)
 Datasheet: [Link](#)
 Item No.: 10120543



MBS (Maintenance Bypass Switch)
 Datasheet: [Link](#)
 Item No.: 10120500



Schuko Input -> IEC C13
 Item Nr.: 91010017



UK Input -> IEC C13
 Item Nr.: 91010029

Swiss Input -> IEC C13



IEC C13 -> IEC C14
 Item Nr.: 91010013



Schuko Input -> IEC C19
 Item Nr.: 91010018

UK Input -> IEC C19
 Item Nr.: 91010030

Swiss Input -> IEC C19



IEC C19 -> IEC C20
 Item Nr.: 91010028



IEC C13 -> IEC C20
 Item Nr.: 91010041



IEC C14 -> IEC C19
 Item Nr.: 91010040



IEC C14 -> Schuko
 Converter
 Item Nr.: 91015003



Schuko -> UK adaptor
 Item Nr.: 91010031

Version: EN 25/08/2014

We reserve the right for technical changes and mistakes